

Kamplex P28F Slim - Mini Soundproof Booth

GENERAL SPECIFICATIONS

DIMENSIONS AND WEIGHT

- Outside (LxWxH): 96 x 74 x 208 cm
- Inside (LxWxH): 81 x 60 x 180 cm
- Ext. sq.m: 0.71
- Weight: 171 Kg

APPLICATIONS

PRO28F line is an excellent noise reduction booth, is recommended for hearing screening and diagnostic tests in audiology centers and shops for those who have limited space available and need a very small soundproof booth. These booths can be also used in temporary situations for occupational medicine, in companies and schools.

EXTERIOR

The exterior finishing is made of a white, highly-resistant, fireproof, washable panel. Also included is an external folding table (79 x 50 cm).

INTERIOR

The interior finishing is made of acoustic pyramid foam in anthracite grey, designed to reduce sound waves for a perfect acoustics. Also included is an internal folding table (79 x 32 cm).

DOOR

The door is reversible with magnetic closing. The opening (right or left) can be decided upon assembling the booth and changed in 5 minutes. Clear opening 55 x 168 cm (w x h).

WINDOW

The window consists of a special double safety glass. Clear view 56x56 cm (w x h).

FLOOR

The floor is layered with different materials and it stands on anti-vibration adjustable feet. Finishing: technical, antistatic, fireproof, washable carpet.

INSTALLATION

Easy and quick to install; no specialized staff required. Just follow the instructions. Thanks to reduced weight and small size can be easily set up in 5 minutes and transported in a station wagon car.

NOTES

The materials are fireproof and self-extinguishing at the origin. Specifications are subject to change without notice. Warranty: limited to one year from delivery date.



PACKAGING

Delivered for shipping in a ISPM wooden case in kit form or pre-built*

* Pre-defined at time of order

POWER

CONNECTING INSTRUMENTS

Cables are laid through a new universal sound proof panel with jack and USB connection. All kinds of cables can be used without the need to be cut. Adaptable to all types of instruments. Hangers for earphones are included.

ELECTRICAL SYSTEM

Lighting is ensured by a lamp with low energy consumption. Power supply: 230 V. 50-60 Hz.

NOISE REDUCTION

PRO28F line is tested at the Technical-Physics Laboratory C.S.I. S.p.A. (Milano-Italy) accredited by ACCREDIA.

*Product conforms with international UNI EN ISO 8253 1:2010 with a background noise no greater than 65dB (at 500Hz) assuming a noise barrier headset (audiocups) is used.

COMPLIANCE/REGULATORY STANDARDS

Medical Device Class I - MDD 93/42/CEE
2007/47/CE - CEI 64/11
CEI 64/8 - 2006/95/CE
UNI EN ISO 8253 1:2010.

ACOUSTIC INSULATION

Frequency (Hz)	Intensity (dB HL)
125	21.7
250	25.6
500	32.6
1000	36.2
2000	34.0
3150	37.7
4000	41.1
6300	41.6
8000	43.0

OPTIONALS

- Audiocups
- Modification Voltage 110 V.
- Vertical window strip (16 x 115 cm)
- Wall audiometer support
- Internal seat
- Kit 4 castors (2 with brake)